

HIGHLIGHTS

- Rotax® V-Twin engine
- Arched double A-arm front suspension with front sway bar
- Front and rear FOX† 1.5 PODIUM† RC2 shocks
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 12 in. (30.5 cm) cast-aluminum beadlock wheels
- 25 in. (63.5 cm) ITP Holeshot ATR tires
- Front & central skid plate
- Aluminum taper-profile handlebar with full wrap handguards
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
- Anti-Lock Braking System (ABS)
- Multifunction digital gauge
- X-package coloration, graphics and seat cover
- RF Digitally Encoded Security System (D.E.S.S.™)



Desert Tan & Carbon Black

ENGINE

| | |
|----------------------|--|
| Type | 44 kW (59 hp), Rotax® 649.6 cc V-twin, liquid cooled |
| Fuel Delivery System | Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) |
| Transmission | CVT, P / R / N / H / L, standard engine braking |
| Drive Train | Selectable 2WD / 4WD with Brake Traction Control (BTC) |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |
| Speed Category | More than 60 km/h |

SUSPENSIONS

| | |
|------------------|--|
| Front Suspension | Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel |
| Front Shocks | FOX† 1.5 PODIUM† RC2 |
| Rear Suspension | Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel |
| Rear Shocks | FOX† 1.5 PODIUM† RC2 |

TIRES / WHEELS

| | |
|-------------|---|
| Front Tires | ITP Holeshot† ATR 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) |
| Rear Tires | ITP Holeshot† ATR 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) |
| Wheels | 12 in. (30.5 cm) cast-aluminum beadlock |

BRAKES

| | |
|-------|---|
| Front | Dual 214 mm disc brakes with hydraulic twin-piston calipers |
| Rear | Single 214 mm disc brake with hydraulic twin-piston caliper |

DIMENSIONS / CAPACITIES

| | |
|------------------------|---|
| Estimated Dry Weight * | 668 lb (303 kg) |
| L x W x H | 86 x 48 x 49 in. (218.4 x 121.9 x 124 cm) |
| Wheelbase | 51 in. (129.5 cm) |
| Ground Clearance | 10.5 in. (26.7 cm) |
| Seat Height | 34.5 in. (87.7 cm) |
| Rack Capacity | Rear: 35 lb (16 kg) |
| Storage Capacity | N/A |
| Towing Capacity | 660 kg trailer with brakes and 335 kg trailer without brakes |
| Fuel Capacity | 5.4 gal (20.5 L) |

FEATURES

| | |
|---------------------|---|
| Gauge | 4.5-in. digital display: Speedometer, tachometer, odometer, trip & hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge & clock |
| Instrumentation | Lighter type DC Outlet in console, standard connector in the back (15-A) |
| Anti-theft System | RF Digitally Encoded Security System (D.E.S.S.™) |
| Lighting | 240 W from 4 fender mounted projector beam headlamps (60-W) with tail light / brake light |
| Winch | N/A |
| T-Category features | Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn |
| Seat | Standard |
| Protection | Front bumper Aluminum taper-profile handlebar with full wrap handguards Front & central skid plate |

WARRANTY

| | |
|------------------|-----------------------------|
| Factory warranty | 2-year BRP limited warranty |
|------------------|-----------------------------|