

# MY23 MAVERICK TRAIL DPS 700 / 1000 T



 Oxford Blue

## HIGHLIGHTS

- Open front differential with Brake Traction Control (BTC)
- Dynamic Power Steering (DPS™)
- Anti-Lock Braking System (ABS)
- Ergoprint seats with color accents
- 12 in. (30.5 cm) cast-aluminum wheels

ENGINES	750	1000
Type	39 kW (52 hp) / 41 lb-ft, Rotax® ACE (Advanced Combustion Efficiency) 650 cc single cylinder, liquid cooled, with catalytic converter	56 kW (75 hp), Rotax® 976 cc, V-twin, liquid cooled, with catalytic converter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	PDrive primary CVT with engine braking and Electronic Drive Belt Protection L / H / N / R / P	Quick Response System (QRS) CVT with high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P
Drive Train	Selectable 2WD / 4WD with Open front diff. with Brake Traction Control (BTC)	
Driving Assistance	Electronic Hill Descent Control SPORT / ECO™ modes	
Power Steering	Dynamic Power Steering (DPS)	
<b>SUSPENSIONS</b>		
Front Suspension	Double A-arm with sway bar / 10 in. (25.4 cm) travel	
Front Shocks	Twin tube gas charged shocks	
Rear Suspension	TTA with sway bar / 10.5 in. (26.7 cm) travel	
Rear Shocks	Twin tube gas charged shocks	
<b>TIRES / WHEELS</b>		
Front & Rear Tires	Carlisle ACT 26 x 8 / 9 x 12 in. (66 x 20.3 / 22.9 x 30.5 cm)	
Wheels	12 in. (30.5 cm) cast-aluminum	
<b>BRAKES</b>		
Front & Rear Brakes	Dual 220 mm disc brakes with hydraulic twin-piston calipers with Dynamic Brake Control (ABS + HHC + HDC) - TCS can be switched off on 1000	

DIMENSIONS / CAPACITIES	750	1000
Estimated Dry Weight *	1,271 lb (576.5 kg)	1,364 lb (618.7 kg)
Chassis / Cage	Profiled cage ROPS approved	
L x W x H	118 x 62.8 x 69 in. (300.5 x 159.6 x 175.3 cm)	
Wheelbase	90.6 in. (230.1 cm)	
Ground Clearance	10 in. (25.4 cm)	
Cargo Box Capacity	300 lb (136 kg)	
Towing Capacity	1,500 lb (682 kg)	
Storage Capacity	Total: 5.3 gal (20.2 L)	
Fuel Capacity	10 gal (38 L)	

## FEATURES

Gauge	7.6 in. (19.3 cm) wide digital display with keypad
Instrumentation	DC outlet (10-A)
Ignition	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Magneto	650-W
Lighting	Front lighting output 110 W LED tail lights with halo glow effect
Winch	N/A
Steering Wheel	Adjustable tilt steering
Protection	Integrated front steel bumper, Full skid plate Mudguards and Mudflaps
Hitch Type	2 in. hitch receiver with rear hitch and tow ball
T-Cat Features	Horn, flashers and position lamps, side mirrors, license plate support, hook on front metal bumper, driver seat detector, low brake fluid sensor, 7-pin trailer connexion (12V)

## WARRANTY

Factory warranty	2-year BRP limited warranty
------------------	-----------------------------



©2022 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. \*Base model dry weight shown. †Visco-Lok is a trademark of GKN Viscodrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

