

MY23 TRAXTER PRO DPS HD10



Tundra Green

ENGINE

| | |
|----------------------|--|
| Type | 61 kW (82 hp) / 69 lb-ft, Rotax® 976 cc, V-twin, liquid cooled |
| Fuel Delivery System | Intelligent Throttle Control (ITC™) with Electronic Fuel Injection (EFI) |
| Transmission | PRO-TORQ CVT Transmission with Quick Response System (QRS), high airflow ventilation and Electronic Drive Belt Protection Extra-L / H / N / R / P |
| Drive Train | Selectable Turf Mode / 2WD / 4WD with Visco-Lok† auto-locking front differential |
| Driving Assistance | Electronic Hill Descent Control ECO™ / ECO™ Off / Work modes |
| Power Steering | Dynamic Power Steering (DPS™) |

SUSPENSIONS

| | |
|------------------|---|
| Front Suspension | Arched double A-arm / 11 in. (27.9 cm) travel |
| Front Shocks | Twin tube gas charged shocks |
| Rear Suspension | Arched TTA with external sway bar / 11 in. (27.9 cm) travel |
| Rear Shocks | Twin tube gas charged shocks |

TIRES / WHEELS

| | |
|--------------------|--|
| Front & Rear Tires | XPS Trail King 27 x 9 / 11 x 14 in. (68.6 x 22.9 / 27.9 x 35.6 cm) |
| Wheels | 14 in. (35.6 cm) cast-aluminum |

BRAKES

| | |
|-------|---|
| Front | Dual 220 mm disc brakes with hydraulic twin-piston calipers |
| Rear | Dual 220 mm disc brakes with hydraulic twin-piston calipers |

HIGHLIGHTS

- Dynamic Power Steering (DPS)
- 64 in. (162.5 cm) wide with Arched A-arm
- 14 in. (35.6 cm) cast-aluminum wheels
- 27 in. (68.6 cm) XPS Trail King tires
- Horn & side mirrors

DIMENSIONS / CAPACITIES

| | |
|------------------------|---|
| Cage | Profiled cage. ROPS approved |
| Estimated Dry Weight * | 1,815 lb (823 kg) |
| L x W x H | 154.1 x 64 x 78 (391.5 x 162.5 x 198.1 cm) |
| Wheelbase | 115.5 in. (294 cm) |
| Ground Clearance | 13 in. (33 cm) |
| Cargo Box Dimensions | 72 x 54.5 x 10 in. (180.3 x 138.4 x 25.4 cm) |
| Cargo Box Capacity | 1,000 lb (454 kg) |
| Power tilt bed | N/A |
| Tailgate Load Capacity | 250 lb (113.4 kg) |
| Storage Capacity | Total: 94 gal (356 L) |
| Towing Capacity | 2,500 lb (1136 kg) |
| Payload Capacity | 1,570 lb (712 kg) |
| Fuel Capacity | 10.6 gal (40 L) |
| Person Capacity | 3 |

FEATURES

| | |
|-----------------|--|
| Gauge | 4.5 in. (11.4 cm) wide digital display |
| Battery | 12-V (18 amp/h) |
| Magneto | 650-W |
| Instrumentation | DC outlet (10-A) |
| Lighting | Front lighting output 140 W LED tail lights |
| Winch | N/A |
| Seat | VERSA-PRO bench seat with passenger seats flipping up, underside hooks |
| Steering Wheel | Adjustable tilt steering |
| Protection | Integrated front steel bumper HMWPE central skid plate |
| Hitch Type | 2-in hitch receiver |

WARRANTY

| | |
|------------------|-----------------------------|
| Factory warranty | 2-year BRP limited warranty |
|------------------|-----------------------------|



©2022 Bombardier Recreational Products Inc. (BRP). All rights reserved. TM, ® and the BRP logo are trademarks of BRP or its affiliates. *Base model dry weight shown. †Visco-Lok is a trademark of GKN ViscoDrive GmbH. ‡All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring any obligation. Ride responsibly. BRP highly recommends that all SSV drivers take a training course. For safety and training information, see your dealer. SSVs can be hazardous to operate. For your safety, the operator and passenger should wear a helmet, eye protection and other protective clothing. Riding and alcohol/drugs don't mix. Never engage in stunt driving. Avoid excessive speeds and be particularly careful on difficult terrain. SSVs with engine sizes of greater than 90cc are recommended for use only by those age 16 and older. Never carry passengers on any SSV not specifically designated for such use. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Some models depicted may include optional equipment.

